



# Eco-Syn C1 5W-30

INTERNATIONAL  
LUBRICANT COMPANY



PRODUCT CODE	PACK SIZE	CARTON QTY
ESC1530.01	1L	6
ESC1530.05	5L	3
ESC1530.20	20L	1
ESC1530.70	70L	1
ESC1530.208	208L	1
ESC1530.100	1000L	1

## DESCRIPTION

International Lubricant Company's Eco-Syn C1 5W-30 is a Full Synthetic 'Low SAPS' ACEA C1, SAE 5W-30 and JASO DL-1 engine oil formulation which can be used in performance petrol, diesel, light duty commercial van applications. Based on officially approved formulas Eco-Syn C1 5W-30 can be used in vehicles with modern Three Way Catalysts (TWC) and Diesel Particulate Filters (DPF's).

## APPLICATIONS

ILC's Eco-Syn C1 5W-30 is designed for use in 4, 6, 8, 10, 12 cylinder motors along with turbocharges or supercharged engines with or without DPF's. Also suited where **Original Equipment Manufacturers** (OEM's) require an ACEA C1, JASO DL-1 rating from the owner's manual/handbook. Designed to extend the oil drain intervals and maximizing fuel economy with its "Low SAPS" formulation.

## BENEFITS

- Low combustion ash build-up (Low SAPS).
- Lowers fuel consumption.
- Extends the life of Diesel Particulate Filters (DPF's)
- Designed for after-treatment applications.
- Engine protecting technology for cleanliness.

## APPROVALS & SPECIFICATIONS

ACEA C1-12/C2-12  
JASO DL-1

Ford WSS-M2C-934-B  
Mazda

Jaguar/Land Rover STJR.03.5005  
Mitsubishi

(Check owners manual before use)

## TYPICAL CHARACTERISTICS

DENSITY  
15°C  
0.851

VISCOSITY  
40°C  
69.20

VISCOSITY  
100°C  
12

VISCOSITY  
INDEX  
171

Updated Oct 2016