



Eco-Syn C2 5W-30

INTERNATIONAL
LUBRICANT COMPANY



PRODUCT CODE	PACK SIZE	CARTON QTY
ESC2530.01	1L	6
ESC2530.05	5L	3
ESC2530.20	20L	1
ESC2530.70	70L	1
ESC2530.208	208L	1
ESC2530.100	1000L	1

DESCRIPTION

International Lubricant Company's Eco-Syn C2 5W-30 is a Full Synthetic 'Low-Mid SAPS' ACEA C2, SAE 5W-30 engine oil formulation required by **Original Equipment Manufacturers (OEM's)** from PSA Peugeot Citroën B71 2290, Fiat 9.55535-S1, Alfa Romeo, Toyota, Honda engines around the world.

APPLICATIONS

ILC's Eco-Syn C2 5W-30 is designed for use in 4, 6, 8, 10, 12 cylinder motors along with turbocharged and supercharged engines that are either petrol, diesel or light commercial van applications. Suited where OEM's require an ACEA C2-A5/B5, API SN/CF rating, refer to the owner's manual/handbook. Developed to extend oil drain intervals and maximize fuel economy.

BENEFITS

- Fuel economy saving technology.
- Extends the life of Diesel Particulate Filters (DPF's)
- Designed for after-treatment applications.
- Engine protecting technology for cleanliness.

APPROVALS & SPECIFICATIONS

ACEA C2-A5/B5
API SN/CF
Alfa Romeo**

Fiat 9.55535-S1
Honda**

PSA Peugeot Citroën B71 2290
Toyota**

(Check owners manual before use)

TYPICAL CHARACTERISTICS

DENSITY 15°C	VISCOSITY 40°C	VISCOSITY 100°C	VISCOSITY INDEX
0.853	61.70	10.50	160

Updated Oct 2016