



Eco-Syn MVA C3 5W-40

INTERNATIONAL
LUBRICANT COMPANY



PRODUCT CODE	PACK SIZE	CARTON QTY
ESMVA540.01	1L	6
ESMVA540.05	5L	3
ESMVA540.20	20L	1
ESMVA540.70	70L	1
ESMVA540.208	208L	1
ESMVA540.100	1000L	1

DESCRIPTION

International Lubricant Company's Eco-Syn MVA C3 5W-40 high performance Full Synthetic petrol and diesel 'Low SAPS' engine oil is equipped to be used in a wide range of **Original Equipment Manufacturers** (OEM's) applications where Diesel Particulate Filters (DPF's) or Three Way Catalyst (TWC) are used.

APPLICATIONS

ILC's Eco-Syn MVA C3 5W-40 can be used in OEM applications from BMW, Mercedes-Benz, Hyundai-Kia and General Motors (Chrysler, Jeep, Dodge, Holden, Opel, Chevrolet), Porsche, Fiat, Renault, Ford. Recommended for use where ACEA C3 is required in petrol, diesel and light duty commercial vans suiting all types of driving conditions from around town, highway or in extreme conditions.

BENEFITS

- Lowers fuel consumption
- Extends the life of Diesel Particulate Filters (DPF's)
- Long drain interval technology
- Low Sulfur, Ash and Phosphorus (Low SAPS) Technology

APPROVALS & SPECIFICATIONS

API SN/CF	Fiat 9.55535-S2	VW 502 00/505 01/505 00
ACEA C3-12	Porsche A40	Renault RN0700/RN0710
BMW LL-04	Ford WSS M2C-917-A	
Dexos2™	MB 229.51/229.31/226.5	

(Check owners manual before use)

TYPICAL CHARACTERISTICS

DENSITY 15°C	VISCOSITY 100°C	VISCOSITY INDEX	FLASH POINT COC°C
0.850	14	175	232

Updated Oct 2016