



ATF DX-3

Automatic Transmission Fluid

INTERNATIONAL
LUBRICANT COMPANY



PRODUCT CODE	PACK SIZE	CARTON QTY
ATFDX3.01	1L	6
ATFDX3.05	5L	3
ATFDX3.20	20L	1
ATFDX3.70	70L	1
ATFDX3.205	205L	1
ATFDX3.100	1000L	1

DESCRIPTION

International Lubricant Company's ATF DX-3 is a high grade automatic transmission fluid designed for use where Dexron® III or Dexron® II fluid are called for. ATF DX-3 is very stable to reduce oxidation, wear, corrosion, foam and has a very high viscosity index along with friction modifiers and outstanding detergent dispersants that allows excellent smooth shift performance.

APPLICATIONS

ILC's ATF DX-3 may be used in passenger car, light duty and heavy duty truck automatic transmissions, power steering units, torque converters, special hydraulic systems on off-road equipment where this type of fluid is specified. ATF DX-3 is recommended in OEM application from Ford, Holden, Toyota, Mitsubishi, Mazda, Volvo along with many more, always refer to the owner's manual/handbook.

BENEFITS

- Excellent smooth shift performance.
- Reduces oxidation, wear and corrosion.
- Very high viscosity index.
- Designed for a wide range of applications.

APPROVALS & SPECIFICATIONS

Dexron IID/F/H
Ford Mercon

Allison C-4
Caterpillar TO-2

ZF TE-ML 14A
MAN 339 Type Z1/V1

(Check owners manual before use)

TYPICAL CHARACTERISTICS

VISCOSITY
40°C
152

VISCOSITY
100°C
17.20

VISCOSITY
INDEX
122

POUR
POINT°C
-21

When using this fluid a complete flush is advised for maximum performance.

Updated Oct 2016