



Air Intake Cleaner Fluid

INTERNATIONAL
LUBRICANT COMPANY

- ① **Working Time:** 25-35 minutes.
- ② **Application:** Both Petrol & Diesel Engines.
- ③ **Usage:** 300ml per application.
- ④ **Usage Intervals:** Every 6-8 months.



DESCRIPTION

International Lubricant Company's Air Intake Cleaner Fluid is a product designed for the Automotive Professionals/Workshops/Garages for use as an additional feature. Produced to clean and remove deposits in air intake systems, throttle valves, combustion chambers, valve seats, inlet and outlet valves while delivering better throttle response and also compression as well as reducing the knocking in engines.

APPLICATIONS

ILC's Air Intake Cleaner Fluid is used with our PSK system (Professional Spray Kit) or Spray Kits with comparable adapters. Before cleaning, perform an oil change on the vehicle first.

- 1) Spray approx. 200ml evenly in all intake ducts by removing the adapter in and out.
- 2) Wait approx. 30 mins for product to clean.
- 3) Start engine and run it at 2500 rpm.
- 4) Use the remaining liquid by spraying in intervals of 5 seconds on/off into the air intake system.

BENEFITS

- Cleans combustion chambers.
- Increase engine performance.
- Reduce fuel consumption.
- Decrease exhaust emissions.

Updated November 2016