



# CH-4 15W-40

INTERNATIONAL  
LUBRICANT COMPANY



PRODUCT CODE	PACK SIZE	CARTON QTY
CH1540.01	1L	6
CH1540.05	5L	3
CH1540.20	20L	1
CH1540.70	70L	1
CH1540.205	205L	1
CH1540.100	1000L	1

## DESCRIPTION

International Lubricant Company's CH-4 15W-40 is a multi-grade diesel engine oil formulated to suit a wide range of applications. Excellent resistance against soot deposits in pipes and turbo engines, while keeping piston rings, valves protected from wear.

## APPLICATIONS

ILC's CH-4 15W-40 is designed for a wide range of on road and off road vehicles from cars, light duty commercial vehicles to off-road 4WD and off-road machinery. This provides versatile oil with an older mixed fleet, ranging from American, European and Japanese engine makers. Used where **Original Equipment Manufacturers** (OEM's) require an API CH-4/SJ, ACEA A3/B4-E3/E5, JASO DH-1, Mercedes-Benz 228.3, Volvo VDS-2, Iveco T2 E5, Renault Trucks RD/RD-2, Mack EO-M Plus, MAN M3275, Cummins CES 20071-72-76, MTU Type 2 rating from the owner's manual/handbook.

## BENEFITS

- Reduces sludge build up.
- Deposit control and corrosion protection technology.
- Safe lubricating film at very high temperatures to ensure good oil flow.

## APPROVALS & SPECIFICATIONS

API CH-4/SJ	Volvo VDS-2	Cummins CES 20071/72/76	Renault Trucks RD/RD-2
ACEA A3/B4-E3/E5	MTU Type 2	MAN M3275	Iveco T2 E5
JASO DH-1	Mack EO-M Plus	Mercedes-Benz MB228.3	

(Check owners manual before use)

## TYPICAL CHARACTERISTICS

DENSITY 15°C	VISCOSITY 40°C	VISCOSITY 100°C	VISCOSITY INDEX
0.888	152	17.20	122

Updated Oct 2016