



# Green Coolant Concentrate

INTERNATIONAL  
LUBRICANT COMPANY



PRODUCT CODE	PACK SIZE	CARTON QTY
GCC.01	1L	6
GCC.05	5L	3
GCC.20	20L	1
GCC.70	70L	1
GCC.208	208L	1
GCC.100	1000L	1

## DESCRIPTION

International Lubricant Company's Green Concentrate Coolant is an Anti-Freeze, Anti-Boil, Long Life organic (Organic Acid Technology, OAT) Type "A" fluid. Formulated with **NO Phosphates, NO Amines, NO Silicates, NO Borates, NO Nitrites and NO Nitrates** allowing outstanding protection from corrosion, rust or cavitation in a cooling system.

## APPLICATIONS

ILC's Green Coolant is designed to be used up to 5 years/500,000 kms in a wide range of OEM applications from American, European, Japanese in passenger cars, light & heavy duty vehicles, 4WD's, Off-Road equipment. Ideally suited as a 50/50 ratio dilution.

## BENEFITS

- Outstanding rust and corrosion protection.
- Contains No Phosphate, No Nitrite, No Amine.
- 5 Year/500 000 km service life.
- Suits a wide range of applications.

## APPROVALS & SPECIFICATIONS

AS 2108.1 : Type A	Ford ESE FM 97B18-C	IVECO	MAN 324 Type SNF
ASTM D3306/D4656/D4985	Ford ESE M 978B4H-A	Japanese JIS K 2234	Porsche
BMW N 600 69.0	Ford ESE M 99B166-C	Kia	SAE J 1034
Cummins 3666132	GM 6277M/1825M/1899M	Mitsubishi	Saab FSD 8074
Caterpillar 1 EO 535	Hyundai	Mercedes Benz MB 325.3	Subaru
DAF 742002	Isuzu	Mazda MES MN 1210	Volvo

(Check owners manual before use)

## TYPICAL CHARACTERISTICS

Glycol by Weight (gm/L)	Density (Concentrate)	Boiling Point (50% by Vol.)	Freeze Point (50% by Vol.)
1.0034	1.1103 kg/L	108.2°C	-36.2°C

Updated Jan 2017