



DPF Demount Cleaning Fluid

INTERNATIONAL
LUBRICANT COMPANY

- ① **Working Time:** approx 7 to 11 hours.
- ② **Application:** Any Diesel Particulate Filter.
- ③ **Usage:** Depending on size of DPF filter.
- ④ **Usage Intervals:** When required.



DESCRIPTION

International Lubricant Company's DPF Demount Cleaning Fluid is a highly concentrated fluid designed to breakdown all contaminants in a Diesel Particulate Filter which have caused limp mode to be activated in a vehicle. This product is the most effective of its kind, cleans, dissolves and removes residue. Allowing clear flow in the DPF bringing it back to its original condition and functions. Most **COST EFFECTIVE WAY** without purchasing a new diesel particulate filter.

APPLICATIONS

- 1) Demount/Remove Particulate filter from vehicle (Mark R on opening which was closest to rear of exhaust).
- 2) Place Particulate Filter vertically inside plastic tub provided (Opening not marked faced down/inside the plastic tub with R marked outside tub).
- 3) Fill DPF Demount cleaning fluid inside opening. (Depending of Filter size, fluid will vary).
- 4) Lay particulate filter down inside fluid which has been added, filter should be submerged in fluid. (If filter is not completely submerged revert back to point 3).
- 5) Allow 7 to 11 hours for cleaning process to take effect.
- 6) Remove particulate filter from fluid, rinse with clean water to remove any residue left.
- 7) Re-assemble the Particulate Filter on vehicle, test drive for about 15-20 mins.

BENEFITS

- Regenerates its full functionality.
- Dissolves and removes contaminants.
- Maximising engine performance.
- Cost effective cleaning method.

Updated November 2016