



INTERNATIONAL
LUBRICANT COMPANY

DPF Spray Gun 2-in-1 Fluid

- ① **Working Time:** Depends on users application.
- ② **Application:** Any Diesel Particulate Filter.
- ③ **Usage:** Suits all Diesel Particulate Filters.
- ④ **Usage Intervals:** When required.



DESCRIPTION

International Lubricant Company's DPF Spray Gun 2-in-1 Fluid is the ideal product for professional workshops to add to their services. Designed as a 2 in 1 application - First it cleans, dissolves and breaks down the contaminants inside a particulate filter. Second it restores and regenerates the particulate filter to its original condition without installing expensive new diesel particulate filters.

This product is designed to be used with our Compressed Air Spray Gun.

APPLICATIONS

Before using this product make sure

ENGINE IS TURNED OFF, EXHAUST SYSTEM IS AT ROOM TEMPERATURE.

- 1) Remove temperature/pressure sensors from the Diesel Particulate Filter.
- 2) Insert Compressed Air Spray Gun probe in the sensor hole which was removed in point 1.
- 3) Add 1 bottle of DPF Spray Gun 2-in-1 Fluid into the tank of the Compressed Air Spray Gun.
- 4) Spray in intervals of 6 seconds On/Off until empty.
- 5) Apply the sensor which was removed, back into its hole.
- 6) Take vehicle for a test drive for about 25mins, loose contaminants will be dissolved while driving and burn off during the regeneration process.
- 7) If the regeneration process does not automatically start, consult your vehicles hand book for further options.

BENEFITS

- Regenerates its full functionality.
- Dissolves and removes contaminants.
- Maximising engine performance.
- Cost effective cleaning method.

Updated November 2016