



Euro Diesel CJ-4 15W-40

INTERNATIONAL
LUBRICANT COMPANY

PRODUCT CODE	PACK SIZE	CARTON QTY
EDJ1540.01	1L	6
EDJ1540.05	5L	3
EDJ1540.20	20L	1
EDJ1540.70	70L	1
EDJ1540.208	208L	1
EDJ1540.100	1000L	1



DESCRIPTION

International Lubricant Company's Euro Diesel CJ-4 15W-40 is a heavy duty diesel engine oil formulated with unique 'Low SAPS' additives that fulfill the latest requirements of **Original Equipment Manufacturers** (OEM's) engines equipped with after-treatment systems using Diesel Particulate Filters (DPF's), Diesel Oxidation Catalyst (DOC) or Exhaust Gas Recirculation (EGR).

APPLICATIONS

ILC's Euro Diesel CJ-4 15W-40 is compatible with the latest after-treatment devices installed from OEM's globally. Suited for use in early and late model engines and can be applied in Euro 5 engines with Selective Catalyst Reduction (SCR) systems that require low ash oil.

BENEFITS

- High performance oil developed for long drain intervals.
- Outstanding anti-wear properties to keep engines clean.
- Safe lubricating film at very high temperatures to ensure good oil flow.
- Effective protection against bore polishing.

APPROVALS & SPECIFICATIONS

API CJ-4/SM	Renault VI RLD-3	Mercedes-Benz MB228.31	MTU Type 2.1
ACEA E7-12/E9-12	Cat ECF-2/ECF-3	Mack EO-O-Premium Plus	Allison C-4
JASO DH-2	Cummins CES 20081	Isuzu (DPF equipped vehicles)	Global DHD-1
Volvo VDS-4	Detroit Diesel 93K218	MAN M3575	Iveco-Scania-DAF
Deutz DQC III-10 LA			

(Check owners manual before use)

TYPICAL CHARACTERISTICS

DENSITY 15°C	VISCOSITY 100°C	VISCOSITY INDEX	FLASH POINT COC°C
0.874	14.50	137	232

Updated Oct 2016