



Extreme HVI Hydraulic 68

INTERNATIONAL
LUBRICANT COMPANY



PRODUCT CODE	PACK SIZE	CARTON QTY
EH068.05	5L	3
EH068.20	20L	1
EH068.70	70L	1
EH068.200	200L	1
EH068.100	1000L	1

DESCRIPTION

International Lubricant Company's Extreme HVI Hydraulic 68 has a High Viscosity Index (HVI) making this hydraulic oil suitable for systems operating under high pressure and high temperatures. Formulated with an extremely high viscosity index and excellent wear preventive properties, this fluid withstands the most extreme operating conditions.

APPLICATIONS

ILC's Extreme HVI Hydraulic 68 is a superior quality tailor-made heavy duty fluid designed for hydraulic systems from earthmoving equipment, civil engineering, agricultural, marine and transport that have to work under high pressure over a wide temperature range.

BENEFITS

- Excellent protection against wear, corrosion or rust.
- Extremely high viscosity.
- Outstanding thermal and oxidative stability properties.
- Very good foam suppressing properties.

APPROVALS & SPECIFICATIONS

DIN 51524-3 HVLP
AFRON NF E 48-603 HV
ISO 11158 HV

ASTM D 6158 HV
Denison HF-0/HF-1/HF-2
GM LS-2

Eaton Brochure 694 for 35VQ25A
Cincinnati Machine P-69

(Check owners manual before use)

TYPICAL CHARACTERISTICS

DENSITY 15°C	VISCOSITY 40°C	VISCOSITY 100°C	VISCOSITY INDEX
0.865	68	11.2	157

Updated Oct 2016