



INTERNATIONAL
LUBRICANT COMPANY

Full Syn ATF MV



PRODUCT CODE	PACK SIZE	CARTON QTY
FSATFMV.01	1L	6
FSATFMV.05	5L	3
FSATFMV.20	20L	1
FSATFMV.70	70L	1
FSATFMV.208	208L	1
FSATFMV.100	1000L	1

DESCRIPTION

International Lubricant Company's Full Syn ATF MV is designed with the latest additive formulations, full synthetic oils and high performance technology giving this product an outstanding viscosity index. Specifically used to protect against wear, corrosion, foaming with friction properties to consequently lower noise and smooth shifting.

APPLICATIONS

ILC's Full Syn ATF MV meets and exceeds the requirements of a wide range of transmissions from Japanese OEM's, American OEM's and in European OEM applications in the toughest conditions globally. Providing not only protection but also compatible with synthetic seals. (Not Suitable for Hybrid CVT or Ford Type F applications).

BENEFITS

- Specific additives to reduce noise.
- Outstanding smooth shifting performance.
- Very low pour point.
- Stable viscosity index.
- Fuel efficient performance oil.

APPROVALS & SPECIFICATIONS

Allison C4	Hyundai/Kia SP-II/SP-III	Toyota T, T-II, T-III, T-IV WS-(JWS 3324)
Aisin Warner AW-1	MAN 339F	VAG G-052 162
BMW 2754	MB 236.1/2/3/5	VAG G-055 005
Dexron II/IIID/IIIE/IIIG/IIIH/VI	Mitsubishi SP-II/SP-III	Volvo 1161540
Ford Mercon V	Nissan Matic Fluid C/D/J/K	ZF TE-ML 03D
Honda ATF-Z1 (except in CVT)	Subaru ATF	ZF TE-ML 11B
		ZF TE-ML 14A

(Check owners manual before use)

TYPICAL CHARACTERISTICS

VISCOSITY 40°C	VISCOSITY 100°C	VISCOSITY INDEX	POUR POINT°C
0.844	7.20	179	-48

Updated Feb 2017