



ST-Hydro 68

INTERNATIONAL
LUBRICANT COMPANY



PRODUCT CODE	PACK SIZE	CARTON QTY
STH068.05	5L	3
STH068.20	20L	1
STH068.70	70L	1
STH068.200	200L	1
STH068.100	1000L	1

DESCRIPTION

International Lubricant Company's ST-Hydro 68 is a high grade mineral hydraulic oil designed to meet the requirements of important manufacturers of hydraulic equipment. Formulated with anti-wear, anti-oxidant, anti-corrosion and anti-foam additives to maximize performance.

APPLICATIONS

ILC's ST-Hydraulic 68 can be used in heavy-duty hydraulic equipment from industrial, commercial to off-road also in light duty gearboxes and bearings where the highest demand is crucial. Suited for use where the hydraulic manufacturers recommend a specific time to service.

BENEFITS

- Excellent stability against oxidation.
- Great protection against wear, rust and corrosion.
- Superior temperature stability.
- Very good anti-foam properties.

APPROVALS & SPECIFICATIONS

DIN 51524-2 HLP
AFRON NF E 48-603 HM
ISO 11158 HM

ASTM D 6158 HM
Denison HF-0/HF-1/HF-2
GM LS-2

Eaton Brochure 694 for 35VQ25A
Cincinnati Machine P-69

(Check owners manual before use)

TYPICAL CHARACTERISTICS

DENSITY
15°C
0.876

VISCOSITY
100°C
8.70

VISCOSITY
INDEX
102

FLASH POINT
COC°C
220

Updated Oct 2016