



Semi-Syn 5W-30

INTERNATIONAL
LUBRICANT COMPANY



PRODUCT CODE	PACK SIZE	CARTON QTY
SS530.01	1L	6
SS530.05	5L	3
SS530.20	20L	1
SS530.70	70L	1
SS530.208	208L	1
SS530.100	1000L	1

DESCRIPTION

International Lubricant Company's Semi Synthetic SAE 5W-30 is a ILSAC GF-5 premium engine oil developed for modern petrol and LPG motors. Formulated using semi synthetic technology making this fluid ideal for fuel saving applications while lowering emissions and extending engine life.

APPLICATIONS

ILC's Semi-Syn 5W-30 is formulated for some manufacturers like Toyota, Ford, Honda, Holden, Mazda, Nissan and Mitsubishi using synthetic technology which calls for an ILSAC GF-5 specification. This fluid is compatible with fuel systems from Petrol, Flexi-fuel, E85, E10 and engines from passenger cars, light duty commercial vehicles from 4, 6, 8 cylinders including turbocharged and supercharged motors along with LPG (Liquefied Petroleum Gas) vehicles keeping it clean and free from harmful deposits.

BENEFITS

- Fuel saving technology.
- Low viscosity providing cold start protection.
- Lowers emissions.
- Multi fuel compatible.
- Extends engine life.
- Reduces engine wear and sludge formation

APPROVALS & SPECIFICATIONS

API SN
ILSAC GF-5

Chrysler MS-6395
Ford WSS-M2C-910-A

Ford WSS-M2C-946-A
Ford WSS-M2C-929-A

(Check owners manual before use)

TYPICAL CHARACTERISTICS

DENSITY
15°C

0.869

VISCOSITY
100°C

11.8

VISCOSITY
INDEX

153

FLASH POINT
COC°C

218

Updated Oct 2016