

Super Gear 85W-140

PRODUCT CODE	PACK SIZE	CARTON QTY
SG85140.01	1L	6
SG85140.05	5L	3
SG85140.20	20L	1
SG85140.70	70L	1
SG85140.208	208L	1
SG85140.100	1000L	1



DESCRIPTION

International Lubricant Company's Super Gear Oil 85W-140 is an extreme pressure gear oil designed for mechanical transmissions both light and heavy duty vehicles. Formulated with high quality base oils and special EP-additives making this product suitable for the most rigorous operating conditions.

APPLICATIONS

ILC's Super Gear Oil 85W-140 has a broad application from automotive, agricultural machinery, civil and construction equipment. This gear oil is used in hypoid differentials under heavy-duty conditions and should be used in transmissions that require an EP-transmission oil.

BENEFITS

- · Extreme smooth shifting performance.
- · Excellent resistance against oxidation.
- · Very high activity against wear corrosion and foam.
- · Outstanding EP-properties.

APPROVALS & SPECIFICATIONS

API GL-5 ZF TE-ML 07A/21A MIL-L-2015D Borg Warner 5M-36

(Check owners manual before use)

TYPICAL CHARACTERISTICS

DENSITY	VISCOSITY	VISCOSITY	FLASH POINT
15°C	100°C	INDEX	COC°C
0.912	27	96	245

Updated Oct 2016