



Super Hydro 46

INTERNATIONAL
LUBRICANT COMPANY

PRODUCT CODE	PACK SIZE	CARTON QTY
SPH046.05	5L	3
SPH046.20	20L	1
SPH046.70	70L	1
SPH046.208	208L	1
SPH046.100	1000L	1



DESCRIPTION

International Lubricant Company's Super Hydro 46 is a Top Tier hydraulic oil having a natural, clear/colourless appearance with a higher viscosity index than the standard hydraulic fluids making it ideal for extending oil drain intervals.

APPLICATIONS

ILC's Super Hydro 46 should be 1st choice for heavy duty hydraulic systems in commercial, off-road or industrial applications along with machinery both mobile and stationary. As servicing is vital to prolong the life of equipment Super Hydro 46 is designed for use where fleets of equipment are present and service intervals are not met on the hours required by hydraulic manufacturers. This fluid has a natural viscosity making it outlast standard hydraulic fluids.

BENEFITS

- Excellent protection against wear corrosion or rust.
- Very high viscosity when compared to standard fluids.
- Longer drain intervals.
- Good compatibility with seals and gaskets made from synthetic materials.

APPROVALS & SPECIFICATIONS

DIN 51524-2 HLP
AFRON NF E 48-603 HM
ISO 11158 HM

ASTM D 6158 HM
Denison HF-0/HF-1/HF-2
GM LS-2

Eaton Brochure 694 for 35VQ25A
Cincinnati Machine P-70

(Check owners manual before use)

TYPICAL CHARACTERISTICS

DENSITY
15°C
0.864

VISCOSITY
100°C
7.02

VISCOSITY
INDEX
112

FLASH POINT
COC°C
234

Updated Oct 2016