



Syn-Tec 0W-40

INTERNATIONAL
LUBRICANT COMPANY



PRODUCT CODE	PACK SIZE	CARTON QTY
ST040.01	1L	6
ST040.05	5L	3
ST040.20	20L	1
ST040.70	70L	1
ST040.208	208L	1
ST040.100	1000L	1

DESCRIPTION

International Lubricant Company's Syn-Tec 0W-40 Full Synthetic API SN/CF, ACEA A3/B4, JASO MA engine oil formulation which can be used for performance petrol, diesel and light duty diesel applications without Diesel Particulate Filters (DPF). Based on officially approved formulation Syn-Tec 0W-40 can be used in the most extreme operating temperatures while providing protection against major causes of engine stress, heat, wear, corrosion and sludge.

APPLICATIONS

ILC's Syn-Tec 0W-40 is designed for use in 4, 6, 8, 10, 12 cylinder motors along with turbocharged and supercharged engines. Syn-Tec 0W-40 can be used where **Original Equipment Manufacturers** (OEM's) require an ACEA A3/B4, API SN/CF, JASO MA rating from the owner's manual/handbook. Developed for extended drain intervals and maximizing fuel economy.

BENEFITS

- Reduces Oil Consumption.
- Strong resistance against oxidation.
- Safe lubricating film for all types of conditions.
- Good detergency and dispersion properties to prevent thermal breakdown.

APPROVALS & SPECIFICATIONS

API SN/CF
ACEA A3/B4

(Check owners manual before use)

BMW LL-01
VW 502 00/ 505 00

Mercedes-Benz MB 229.3
Porsche A40

TYPICAL CHARACTERISTICS

DENSITY
15°C
0.846

VISCOSITY
100°C
14

VISCOSITY
INDEX
172

FLASH POINT
COC°C
232

Updated Oct 2016