

Syn-Tec 5W-30

PRODUCT CODE	PACK SIZE	CARTON QTY
ST530.01	1L	6
ST530.05	5L	3
ST530.20	20L	1
ST530.70	70L	1
ST530.208	208L	1
ST530.100	1000L	1



DESCRIPTION

International Lubricant Company's Syn-Tec 5W-30 is a Full Synthetic API SN/CF, ACEA A3/B4 engine oil formulation which can be used for performance petrol, diesel and light duty diesel applications without Diesel Particulate Filters (DPF). Based on officially approved formulation Syn-Tec 5W-30 can be used in the most extreme operating temperatures while providing protection against major causes of engine failure, stress, heat, wear, corrosion and sludge.

APPLICATIONS

ILC's Syn-Tec 5W-30 is designed for use in 4, 6, 8, 10, 12 cylinder motors along with turbocharged and supercharged engines. Syn-Tec 5W-30 can be used where *Original Equipment Manufacturers* (OEM's) require an ACEA A3/B4, API SN/CF rating from the owner's manual/handbook. Developed for extended drain intervals and maximizing fuel economy also suited on LPG and Dual fuel applications.

BENEFITS

- · Reduces Oil Consumption.
- · Strong resistance against oxidation.
- Safe lubricating film for all types of conditions.
- Good detergency and dispersion properties to prevent thermal breakdown.

APPROVALS & SPECIFICATIONS

API SN/CF ACEA A3/B4 BMW LL-01 Mercedes-Benz MB 229.5 VW 502 00/505 00

(Check owners manual before use)

TYPICAL CHARACTERISTICS

DENSITY	VISCOSITY	VISCOSITY	FLASH POINT
15°C	100°C	INDEX	COC°C
0.858	14.40	172	223

Updated April 2017