



# Syn-Tec GF-5 5W-30

INTERNATIONAL  
LUBRICANT COMPANY



PRODUCT CODE	PACK SIZE	CARTON QTY
STGF530.01	1L	6
STGF530.05	5L	3
STGF530.20	20L	1
STGF530.70	70L	1
STGF530.208	208L	1
STGF530.100	1000L	1

## DESCRIPTION

International Lubricant Company's Syn-Tec GF-5 5W-30 is an API SN, ILSAC GF-5 engine oil formulation that can be used in performance petrol and fuel-efficient rating applications. Based on officially approved formulation Syn-Tec GF-5 5W-30 can be used in GM, Ford, Subaru, Chrysler/Jeep, Nissan, Mazda, Honda, Toyota applications under the most extreme operating temperatures while providing protection against major causes of engine failure, heat, stress, wear, corrosion and sludge. *[Not Suited for Diesel Particulate Filters (DPF's)].*

## APPLICATIONS

ILC's Syn-Tec GF-5 5W-30 is designed for use in 4, 6, 8, 10, 12 cylinder motors along with turbocharged, supercharged and fuel economy engines. Syn-Tec GF-5 5W-30 can be used where **Original Equipment Manufacturers** (OEM's) require an API SN or ILSAC GF-5 rating from the owner's manual/handbook. Developed for extended oil drain intervals and maximizing fuel economy. Also suits vehicles equipped for E85 and Flexi-fuel. *[Not Suited for Diesel Particulate Filters (DPF's)].*

## BENEFITS

- Extends oil drain intervals.
- Enhance fuel-efficient technology.
- Oxygen and Catalyst protection sensor friendly.
- Maximizing engine protection.

## APPROVALS & SPECIFICATIONS

API SN  
Dexos1™

ILSAC GF-5  
Ford WSS-M2C-946-A

(Check owners manual before use)

## TYPICAL CHARACTERISTIC

DENSITY 15°C	VISCOSITY 100°C	VISCOSITY INDEX	FLASH POINT COC°C
0.845	10.9	162	228

Updated Oct 2016