



Top 15W-40

INTERNATIONAL
LUBRICANT COMPANY



PRODUCT CODE	PACK SIZE	CARTON QTY
MT1540.01	1L	6
MT1540.05	5L	3
MT1540.20	20L	1
MT1540.70	70L	1
MT1540.200	200L	1
MT1540.100	1000L	1

DESCRIPTION

International Lubricant Company's Top 15W-40 is a high performing API SN/CF rated multi-grade oil used in a wide range of modern motor vehicles. With its high detergent properties, good thermal stability and oxidation resistance designed for all types of climates and driving conditions.

APPLICATIONS

ILC's Top 15W-40 is designed for use in 4,6,8 cylinders along with petrol, light duty diesel and LPG engines. Specifically suited for vehicles with or without turbo or supercharges. Meets the standards of **American Petroleum Institute** (API) as well as many other manufacturers specifications. With its excellent and strong lubricating power this oil helps reduce oxidation, sludge and soot build up.

BENEFITS

- Good detergency prevents deposits in engines.
- Powerful action against wear, corrosion and foam.
- Increases life of engine components.
- Long term engine protection.

APPROVALS & SPECIFICATIONS

API SN/CF

ACEA A3/B4

(Check owners manual before use)

TYPICAL CHARACTERISTICS

DENSITY 15°C	VISCOSITY 100°C	VISCOSITY INDEX	FLASH POINT COC°C
0.888	17.20	122	230

Updated Oct 2016